

NSN 5905-00-491-4659 Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-491-4659 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established liilength: 1.625 inches **Body Diameter:** Between 1.124 inches and 1.156 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 

0.375 inches

**Body Length:** 

Between 0.593 inches and 0.625 inches

liidiameter:

Between 1.124 inches and 1.156 inches

**Shaft Style:** 

Round

**Shaft Bearing Type:** 

Sleeve

**Actuator Type:** 

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:** 

292.0

**Maximum Starting Torque:** 

6.00 inch-ounces

**Maximum Running Torque:** 

6.00 inch-ounces

**Maximum Stop Torque:** 

192.00 inch-ounces

**Nonturn Device Location:** 

At 3 oclock and at 9 oclock

**Nonturn Device Radius:** 

0.531 inches

Mechanical Backlash In Deg Angular Rotation:

1.5

**Fragility Factor:** 

Moderately rugged

## NSN 5905-00-491-4659

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.2 megohms single section
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0 to 12.5 -55 degrees celsius single section and +0.0 to 6.3 -25 degrees celsius single section and +0.0 to 3.1 0 degrees celsius single
section and -4.4 to 4.4 85 degrees celsius single section and +0.0 to 9.4 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
- <del>-</del>
Demilitarization:
No
Fiig:
A002a0