Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-491-4660

Section	Quantity:

1

Body Style: Cylindrical bushing mounted Reliability Indicator: Not established Iiilength: 1.625 inches Body Diameter: Between 1.124 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.250 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.375 inches

Body Length:

Between 0.593 inches and 0.625 inches

liidiameter:

Between 1.124 inches and 1.156 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

292.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

192.00 inch-ounces

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

0.531 inches

Mechanical Backlash In Deg Angular Rotation:

1.5

Fragility Factor:

Moderately rugged

NSN 5905-00-491-4660

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter: 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.0 megohms single section **Rotary Actuator Travel In Angular Deg:** 312.0 **Resistance Tempurature Characteristic Range Per Section In Percent:** +0.0 to 12.5 -55 degrees celsius single section and +0.0 to 6.3 -25 degrees celsius single section and +0.0 to 3.1 0 degrees celsius single section and -4.4 to 4.4 85 degrees celsius single section and +0.0 to 9.4 120 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 2.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0