

View Online at <https://aerobasegroup.com/nsn/5905-00-491-8928>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

4.630 inches

**Mounting Bushing Length:**

0.375 inches

**Undercut Diameter:**

0.125 inches

**Shaft Style:**

Round, stepped

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Dual concentric

**Maximum Starting Torque:**

12.00 inch-ounces

**Maximum Running Torque:**

12.00 inch-ounces

**Switch Contact Arrangement:**

Single pole, single throw, normally open, both positions maintained

**Fragility Factor:**

Moderately rugged

**Undercut Length:**

0.630 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear-bottom

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

500.0 kilohms single section

**Resistance Tolerance Per Section In Percent:**

-30.0 to 30.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0