## NSN 5905-00-491-9893

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-491-9893 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 2.8740 inches and 2.8750 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** Between 2.874 inches and 2.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.500 inches **Body Length:** 1.250 inches **Mounting Lip Diameter:** 3.0000 inches **Mounting Lip Depth:** Between 0.0870 inches and 0.0980 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 348.0 and 352.0 **Maximum Starting Torque:** 2.75 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 

0.001 inches **Lateral Runout:** 0.003 inches

## NSN 5905-00-491-9893

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Pilot Diameter Runout:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.2
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Flange
Electrical Resistance Per Section:
150.0 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:
Between 348.0 and 352.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
3.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 1st section
Tap Location Tolerance Per Section:
-3.0/+3.0 ohms 1st section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 all sections
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
75000.0 1st section
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
60.0 all sections
Terminal Type And Quantity:
7 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0