## NSN 5905-00-492-5430

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-492-5430

Electrical Resistance: 143.000 kilohms Resistance Tolerance In Percent: 4.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Skyle Designator:
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.500 inches Body Diameter: -0.250 inches Body Length: -0.750 inches Power Dissipation Rating In Watts: -0.500 free air Style Designator:
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -70.0 Tempurature Range Of Tempurature Coefficient In Deg C
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 to 150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 to 150.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead Reliability Indicator: Not established  Terminal Length: 1.500 inches  Body Diameter: 0.250 inches  Body Length: 0.750 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 to 150.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length:  1.500 inches Body Diameter:  0.250 inches Body Length:  0.750 inches Power Dissipation Rating In Watts:  0.500 free air  Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  15.0 to 150.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0 to 150.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Hermetically sealed Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length: 1.500 inches  Body Diameter: 0.250 inches  Body Length: 0.750 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Reliability Indicator: Not established  Terminal Length: 1.500 inches  Body Diameter: 0.250 inches  Body Length: 0.750 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:
Not established  Terminal Length:  1.500 inches  Body Diameter:  0.250 inches  Body Length:  0.750 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:
Terminal Length: 1.500 inches Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
1.500 inches  Body Diameter: 0.250 inches  Body Length: 0.750 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:
Body Diameter:  0.250 inches  Body Length:  0.750 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:
0.250 inches  Body Length: 0.750 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
0.750 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:
Power Dissipation Rating In Watts:  0.500 free air  Style Designator:
0.500 free air  Style Designator:
Style Designator:
Axial terminal each end
Test Data Document:
18876-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
. <del>-</del>
Demilitarization:
No
Fiig:
A001a0