Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-492-7771

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

1.688 inches

#### **Body Diameter:**

0.500 inches

### Shaft Diameter:

0.093 inches

#### Shaft Length:

0.563 inches

### Mounting Bushing Length:

# 0.241 inches

**Body Length:** 

1.000 inches

#### Overall Diameter:

0.500 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

0.80 inch-ounces

#### Maximum Running Torque:

0.60 inch-ounces

#### Maximum Stop Torque:

20.00 inch-ounces

#### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Standard bushing



Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0