

View Online at <https://aerobasegroup.com/nsn/5905-00-492-7841>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

0.415 inches

Overall Height:

0.375 inches

Overall Width:

0.160 inches

Mounting Slot Width:

0.074 inches

Shaft Diameter:

0.060 inches

Shaft Length:

0.040 inches

Body Length:

0.375 inches

Body Width:

0.145 inches

Body Height:

0.375 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Nonturn Device Location:

At 4:30 oclock

Nonturn Device Radius:

0.175 inches

Fragility Factor:

Moderately rugged

Lateral Distance Between Mounting Hole Centers:

0.419 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Slot

Features Provided:

Humidity proof

Cubic Measure:

0.023 cubic inches

Electrical Resistance Per Section:

500.000 ohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-10.0 to 10.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0