NSN 5905-00-493-1211

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-493-1211

Electrical Resistance: 1,500 kilohms Resistance Tolerance in Percent: 3,000/4-3,000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Inclosure Method: Incapsulated Reliability Indicator: Wire lead Reliability Indicator: Vict estabilished 30dy Diameter: 1,250 inches 30dy Length: 1,500 inches 70wer Dissipation Rating in Watts: 2,000 free air Style Dasignator: Axial terminal each end Fest Data Document: 1,9902-298a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1,940 inches 1,94	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 3,00043,000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 Tempurature Range Of Tempurature Range R	-20.0/+20.0
Resistance Tolerance In Percent: 3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+275.0 Tempurature Method: 100.000 Ambient Type: 100.000 Ambie	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 125.0/+275.0 Inclosure Method: Incapsulated Terminal Type: Wive lead Reliability Indicator: Not established Rody Length: 1.050 inches Rody Length: 1.0500 inches Power Dissipation Rating in Watts: 1.000 free air Ryle Designator: 1.0301 free air 1.0302-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1.0401 excels any specification, standard or other document that may be referenced in a basic governing drawing) 1.0411 for Measure: 1.0401 fees Incapsulate Incaps	1.500 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 12	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg	-3.000/+3.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Ferminal Type: Write lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 10.500 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Avial terminal each end Fest Data Document: 129902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 12xiculous any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Perpurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Perminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 10.500 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Pest Data Document: 129902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 129x01 free: 12ydit Of Measure: 13ydit Of Measure: 14ydit Of Measure: 15ydit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 10.250 inches Body Diameter: 10.250 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avail terminal each end Test Data Document: 29902-2893651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; oxiculdes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Julit Of Measure: Demilitarization: No Enig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Diameter: 0.250 inches Power Dissipation Rating in Watts: 0.000 free air Style Designator: Axial terminal each end Fest Data Document: 0.9990-2-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 0.050 inches Designator: 0.451 Iteminal each end Fest Data Document: 0.9990-2-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 0.050 inches Designator: 0.9990-2-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 0.9900-2-289a651 drawing (this is the document that may be referenced in a basic governing drawing) 0.9900-2-289a651 drawing (this is the document that may be referenced in a basic governing drawing) 0.9900-2-289a651 drawing (this is the document that may be referenced in a basic governing drawing) 0.9900-2-289a651 drawing (this is the document that may be referenced in a basic governing drawing) 0.9900-2-289a651 drawing (this is the document that may be referenced in a basic governing drawing) 0.9900-2-289a651 drawing (this is the document that may be referenced in a basic governing drawing) 0.9900-2-289a651 drawing (this is the document that may be referenced in a basic governing drawing) 0.9900-2-2	275.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 3ody Diameter: 1.250 inches 3ody Length: 1.500 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Akial terminal each end Fest Data Document: 29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.000 free air Style Designator: Avial terminal each end Fest Data Document: 0.29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 0.200 free in the contractor of the contractor of the contractor drawing) Shelf Life: Via Unit Of Measure:	-55.0/+275.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Juit Of Measure: - Demilitarization: No	Inclosure Method:
Wire lead Reliability Indicator: Not established Rody Diameter: 0.250 inches Rody Length: 0.500 inches Power Dissipation Rating In Watts: 0.000 free air Rely Length: 0.4xial terminal each end Fest Data Document: 0.29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 0.0xial terminal each end Fest Data Document: 0.000 free air 0.000 free Data Document: 0.000 free Data Document: 0.000 free Data Document: 0.000 free Data Document 0.000 free Data Data Document 0.000 free Data Document 0.000 free Data Document 0	Encapsulated
Reliability Indicator: Not established Body Diameter: D. 250 inches Body Length: D. 500 inches Power Dissipation Rating In Watts: Power Dissipation Rating In Watts: Reliability Indicator: Style Designator: Avail terminal each end Fest Data Document: Power Dissipation (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; Excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Nota Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established Body Diameter: Diagony Diameter: Diagony Length: Dissipation Rating In Watts: Dissipation Rating In Watt	Wire lead
Body Length: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.000 free air Style Designator: Axial terminal each end Fest Data Document: 0.29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the basic governing drawing (this is the basic governing drawing) 0.000 free in the ba	Reliability Indicator:
2.250 inches 3.30dy Length: 2.500 inches 2.5	Not established
Body Length: 0.500 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 20xcludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Body Diameter:
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 29902-189a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 29902-189a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 29902-189a651 drawing (this is the basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	0.250 inches
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: A/a Juit Of Measure: - Demilitarization: No Fiig:	Body Length:
2.000 free air Style Designator: Axial terminal each end Fest Data Document: 29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Filg:	0.500 inches
Style Designator: Axial terminal each end Fest Data Document: 29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: V/a Jnit Of Measure: Demilitarization: No Fig:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	2.000 free air
Fest Data Document: 29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Style Designator:
29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Test Data Document:
Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fiig:	29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Jnit Of Measure: - Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Jnit Of Measure: - Demilitarization: No -iig:	Shelf Life:
- Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
A001a0	Fiig:
	A001a0