NSN 5905-00-493-1216

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-493-1216

-20.0/+20.0 Electrical Resistance: 150.000 ohms Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end
Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
-55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Not established Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Body Diameter: 0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
0.093 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
0.312 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Power Dissipation Rating In Watts: 0.500 free air Style Designator:
0.500 free air Style Designator:
Style Designator:
Avial terminal each end
7 Mar terminal each one
Test Data Document:
29902-289a651 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0