NSN 5905-00-493-4934

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-493-4934 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.655 inches **Body Diameter:** 0.890 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.905 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.750 inches **Overall Diameter:** 1.070 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.80 inch-ounces **Maximum Running Torque:** 0.80 inch-ounces **Maximum Stop Torque:** 36.00 inch-ounces **Shaft End Play:**

0.01000 inches

Shaft Runout:
0.003 inches

Lateral Runout:
0.004 inches

Pilot Diameter Runout:
0.00400 inches

NSN 5905-00-493-4934

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.002 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.20/+0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
49956-482135 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 5905-00-493-4934

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0