## NSN 5905-00-493-6015

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-493-6015

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
liilength:
0.312 inches
Terminal Length:
0.481 inches
liiheight:
0.312 inches
liiwidth:
0.726 inches
Body Length:
0.312 inches
Body Width:
0.195 inches
Body Height:
0.312 inches
Actuator Type:
Flush drive with slot-hole
Maximum Starting Torque:
3.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0 to 70.0 single section

0.6 free air single section

**Power Dissipation Rating Per Section In Watts:** 

## NSN 5905-00-493-6015

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: