NSN 5905-00-494-4770

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-494-4770 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.6240 inches and 0.6250 inches Pilot Length: 0.0620 inches **Overall Length:** 1.955 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.7180 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.375 inches **Body Length:** 1.580 inches **Overall Diameter:** 1.063 inches **Mounting Lip Diameter:** 0.7850 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:**

0.40 inch-ounces

0.30 inch-ounces

Maximum Running Torque:



NSN 5905-00-494-4770

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:					
96.00 inch-ounces					
Shaft End Play:					
0.00300 inches					
Shaft Runout:					
0.001 inches					
Lateral Runout:					
0.003 inches					
Pilot Diameter Runout:					
0.00150 inches					
Shaft Radial Play:					
0.002 inches					
Mechanical Backlash In Deg Angular Rotation:					
1.0					
Terminal Location:					
Longitudinally positioned on the circumference					
Mounting Method:					
Clamp ring					
Electrical Resistance Per Section:					
10.000 kilohms single section					
Rotary Actuator Travel In Angular Deg:					
3600.0					
Function Conformity Tolerance Per Section:					
-0.20/+0.20 single section					
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:					
125.0 single section					
Power Dissipation Rating Per Section In Watts:					
2.5 free air single section					
Function Conformity Per Section:					
Single section independent linearity					
Resistance Tolerance Per Section In Percent:					
-3.0/+3.0 single section					
Actuator Travel Control Feature:					
Stops					
Function Characteristic Per Section:					
Single section linear					
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:					
-20.0/+20.0 single section					
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:					
70.0 single section					
Terminal Type And Quantity:					
3 solder stud					
Shelf Life:					
N/a					

NSN 5905-00-494-4770

Precision Wire Wound Variable Resistor - Page 3 of 3



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0