Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-494-4837

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.783 inches

#### Shaft Diameter:

0.156 inches

#### Shaft Length:

0.312 inches

#### Body Length:

0.328 inches

#### Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

300.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### Mounting Method:

Tab

### Features Provided:

Nonmetallic shaft

#### **Electrical Resistance Per Section:**

800.0 ohms single section

### **Rotary Actuator Travel In Angular Deg:**

300.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

# Power Dissipation Rating Per Section In Watts:

0.3 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

# Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

# Standard Taper Curve Per Section:

A single section



Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0