NSN 5905-00-494-9033

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-494-9033 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.556 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.315 inches **Body Length:** 0.681 inches **Overall Diameter:** 1.261 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 0.20 inch-ounces **Maximum Running Torque:** 0.20 inch-ounces **Shaft End Play:** 0.00300 inches **Shaft Runout:** 0.001 inches **Shaft Radial Play:** 0.004 inches **Screw Thread Diameter:**

0.375 inches

Screw Thread Series Designator:
Unef

Screw Thready Qty Per Inch (tpi):
32.0

NSN 5905-00-494-9033 Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
350.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
01220-c52000301 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0