NSN 5905-00-495-8101

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-495-8101 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 1.515 inches **Undercut Diameter:** 1.87500 inches **Undercut Width:** 0.0800 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** Between 0.590 inches and 0.650 inches **Shaft Length:** Between 0.2494 inches and 0.2497 inches **Body Length:** 0.865 inches **Overall Diameter:** 2.205 inches **Mounting Lip Diameter:** 2.0050 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:**

1.00 inch-ounces
Shaft End Play:

0.005 inches

NSN 5905-00-495-8101

A002a0

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Shaft Runout:
0.001 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section equation
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
49956-463736 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: