NSN 5905-00-496-1236

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-496-1236 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6245 inches Pilot Length: 0.0620 inches **Overall Length:** 1.486 inches **Undercut Diameter:** 0.780 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.12475 inches **Shaft Length:** 0.410 inches **Body Length:** 1.076 inches **Overall Diameter:** 0.875 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1088.0 **Maximum Starting Torque:**

0.50 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

NSN 5905-00-496-1236

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
48.00 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.0005 inches
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
1.0 ohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
544.0 single section
Rotary Actuator Travel In Angular Deg:
1220.0
Function Conformity Tolerance Per Section:
-0.08/+0.08 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Test Data Document:
02987-1496624 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-496-1236

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0