NSN 5905-00-496-3700

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-496-3700 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 1.874 inches **Undercut Diameter:** 0.750 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.500 inches **Body Length:** 1.374 inches **Overall Diameter:** 1.250 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 353.0 **Maximum Starting Torque:**

0.20 inch-ounces

Maximum Running Torque:

0.06 inch-ounces

NSN 5905-00-496-3700

Precision Wire Wound Variable Resistor - Page 2 of 3



| Shaft End Play: | | | | | |
|---|--|--|--|--|--|
| 0.00500 inches | | | | | |
| Shaft Runout: | | | | | |
| 0.002 inches | | | | | |
| Lateral Runout: | | | | | |
| 0.002 inches | | | | | |
| Pilot Diameter Runout: | | | | | |
| 0.00200 inches | | | | | |
| Shaft Radial Play: | | | | | |
| 0.002 inches | | | | | |
| Terminal Location: | | | | | |
| Radially positioned over less than half the circumference | | | | | |
| Mounting Method: | | | | | |
| Clamp ring | | | | | |
| Features Provided: | | | | | |
| Humidity proof | | | | | |
| Electrical Resistance Per Section: | | | | | |
| 50.000 kilohms all sections | | | | | |
| Rotary Actuator Travel In Angular Deg: | | | | | |
| 360.0 | | | | | |
| Function Conformity Tolerance Per Section: | | | | | |
| -0.50/+0.50 all sections | | | | | |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: | | | | | |
| 105.0 all sections | | | | | |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: | | | | | |
| -20.0/+20.0 single section | | | | | |
| Power Dissipation Rating Per Section In Watts: | | | | | |
| 1.75 free air all sections | | | | | |
| Function Conformity Per Section: | | | | | |
| All sections independent linearity | | | | | |
| Resistance Tolerance Per Section In Percent: | | | | | |
| -5.0/+5.0 all sections | | | | | |
| Actuator Travel Control Feature: | | | | | |
| Continuous motion | | | | | |
| Function Characteristic Per Section: | | | | | |
| All sections linear | | | | | |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: | | | | | |
| 40.0 all sections | | | | | |
| Precious Material And Location: | | | | | |
| Terminals gold | | | | | |
| Precious Material: | | | | | |
| Gold | | | | | |
| Terminal Type And Quantity: | | | | | |

6 turret

NSN 5905-00-496-3700

Precision Wire Wound Variable Resistor - Page 3 of 3



| SI | nel | lf I | l if | ρ. |
|----|-----|------|------|----|
| Ο. | | • | | v. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0