## NSN 5905-00-496-7473

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-496-7473 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 1.094 inches **Terminal Length:** 0.750 inches **Overall Height:** 0.312 inches **Overall Width:** 0.296 inches **Body Length:** 0.344 inches **Body Width:** 0.296 inches **Body Height:** 0.312 inches **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Maximum Starting Torque:** 4.00 inch-ounces **Maximum Stop Torque:** 8.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear-bottom **Mounting Method: Terminal Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 300.0

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.100 inches

## NSN 5905-00-496-7473

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-70.0 to 70.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.6 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops and spring

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

60.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A002a0