NSN 5905-00-497-0728

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-497-0728

Electrical Resistance: 75.000 ohms Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Incapsulated Iterminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Impurature Method: Impurature Method: Impurature Range Of Tempurature Coefficient In Deg Celsius: Reliability Indicator: Impurature Rate Level In Percent: 0.100 Impurature Rate Level In Percent: 0.090 inches
Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 If empurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated If erminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.100 Body Diameter: 10.090 inches Body Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.100 Rody Diameter: 10.090 inches Rody Length: 10.250 inches
Iso.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.100 Body Diameter: 10.090 inches Body Length: 10.250 inches
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Incapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
0.100 Body Diameter: 0.090 inches Body Length: 0.250 inches
Body Diameter: 0.090 inches Body Length: 0.250 inches
0.090 inches Body Length: 0.250 inches
Body Length: 0.250 inches
0.250 inches
Device Discinction Deting In Wetter
Power Dissipation Rating In Watts:
0.250 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0