Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-497-0732

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# Reliability Indicator:

Not established

## **Overall Length:**

4.457 inches

#### **Terminal Length:**

0.725 inches

#### First Flat Length:

1.500 inches

## Flat Height:

0.344 inches

#### **Body Diameter:**

# 6.090 inches

Shaft Diameter:

0.375 inches

## Shaft Length:

2.000 inches

# Mounting Bushing Length:

0.375 inches

#### **Body Length:**

2.410 inches

#### **Overall Diameter:**

6.815 inches

#### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

# Maximum Starting Torque:

160.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

#### Screw Thread Diameter:

0.250 inches

# Screw Thread Series Designator:

Unc

# Screw Thready Qty Per Inch (tpi):

20.0

# Mounting Facility Quantity:

2



**Terminal Location:** 

Radially positioned over less than half the circumference

#### **Mounting Method:**

Threaded hole

#### **Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:** 

50.000 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

315.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

390.0 single section

Power Dissipation Rating Per Section In Watts:

300.0 heat sink single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

## **Actuator Travel Control Feature:**

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

## **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 tab, solder lug

**Specification Data:** 

81349-mil-r-22/11 government specification

Shelf Life:

N/a

#### Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A002a0