Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-497-0832

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.812 inches

Body Diameter:

1.312 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.313 inches

Body Length:

0.750 inches

Overall Diameter:

1.312 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

352.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

0.70 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.562 inches

Shaft End Play:

0.00700 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.003 inches



Pilot Diameter Runout: 0.00250 inches Shaft Radial Play: 0.004 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 2.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 3 turret Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

NSN 5905-00-497-0832

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

