

View Online at https://aerobasegroup.com/nsn/5905-00-497-1004

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-10.0/+10.0

#### **Electrical Resistance:**

10.000 kilohms

#### **Resistance Tolerance In Percent:**

-0.100/+0.100

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-65.0/+145.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

#### \_ .. . ... . ..

Reliability Indicator:

## Established

**Reliability Failure Rate Level In Percent:** 

0.010

#### **Terminal Length:**

1.500 inches

#### Body Diameter:

0.375 inches

### Body Length:

0.750 inches

#### **Power Dissipation Rating In Watts:**

0.333 free air

#### Cubic Measure (non-core):

0.105 cubic inches

#### Style Designator:

Axial terminal each end

# Test Data Document:

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-r-39005/2 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5905-00-497-1004

Noninductive Wire Wound Fixed Resistor - Page 2 of 2

Fiig: A001a0

