Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-497-1055

Section	Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.187 inches

Shaft Diameter:

0.093 inches

Shaft Length:

0.080 inches

Body Length:

0.375 inches

Body Width:

# 0.190 inches

**Body Height:** 

0.375 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

8280.0

#### **Center To Center Distance Between Terminals:**

0.200 inches

#### **Terminal Location:**

Left adjacent side two rows

**Mounting Method:** 

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

## **Electrical Resistance Per Section:**

20.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

8280.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

# NSN 5905-00-497-1055

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.75 free air single section

## **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

# Actuator Travel Control Feature:

Clutch

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

#### Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A002a0