NSN 5905-00-498-3371

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-498-3371 **Section Quantity:**

1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.320 inches **Terminal Length:** 0.500 inches **Overall Height:** 0.820 inches **Overall Width:** 0.195 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.110 inches **Shaft Length:** 0.070 inches **Body Length:** 1.250 inches **Body Width:** 0.195 inches **Body Height:** 0.320 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:**

0.900 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

Terminal Location:

Lower adjacent side two rows

NSN 5905-00-498-3371

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
2.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.700 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0