Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-498-5505

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

### **Overall Length:**

1.313 inches

#### **Terminal Length:**

0.188 inches

#### **Overall Height:**

0.501 inches

### **Overall Width:**

0.280 inches

#### Mounting Hole Diameter:

# 0.086 inches

Shaft Diameter:

0.125 inches

#### Shaft Length:

0.063 inches

# Body Length:

1.250 inches

#### Body Width:

0.280 inches

#### **Body Height:**

0.313 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

9000.0

# Center To Center Distance Between Terminals:

0.688 inches

# Lateral Distance Between Mounting Hole Centers:

1.000 inches

# Mounting Facility Quantity:

2

#### **Terminal Location:**

Lower adjacent side two rows

## Mounting Method:

Unthreaded hole



**Center To Center Distance Between Terminal Rows:** 0.094 inches **Electrical Resistance Per Section:** 50.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.328 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0