## NSN 5905-00-498-5873

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-498-5873

0.00.00.00
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.4400 inches
Pilot Length:
0.0400 inches
Overall Length:
2.032 inches
Undercut Diameter:
0.440 inches
Undercut Width:
0.0570 inches
Body Diameter:
0.510 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.470 inches
Body Length:
1.272 inches
Overall Diameter:
0.510 inches
Mounting Lip Diameter:
0.5000 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
1080.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:

0.40 inch-ounces

## NSN 5905-00-498-5873

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
100.00 inch-ounces
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
1265.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section terminal base linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-5.0/+5.0 ohms single section
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Clutch
Tap Location From Ccw Terminal Per Section In Ohms:
5000.0 single section
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section

Shelf Life: N/a

4 tab, solder lug

**Terminal Type And Quantity:** 

## NSN 5905-00-498-5873

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0