NSN 5905-00-498-5873

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-498-5873

| 0.00.00.00 |
|--------------------------------------------------------|
| Section Quantity: |
| 1 |
| Body Style: |
| Cylindrical servo mounted |
| Reliability Indicator: |
| Not established |
| Pilot Diameter: |
| 0.4400 inches |
| Pilot Length: |
| 0.0400 inches |
| Overall Length: |
| 2.032 inches |
| Undercut Diameter: |
| 0.440 inches |
| Undercut Width: |
| 0.0570 inches |
| Body Diameter: |
| 0.510 inches |
| Shaft Diameter: |
| 0.125 inches |
| Shaft Length: |
| 0.470 inches |
| Body Length: |
| 1.272 inches |
| Overall Diameter: |
| 0.510 inches |
| Mounting Lip Diameter: |
| 0.5000 inches |
| Mounting Lip Depth: |
| 0.0620 inches |
| Shaft Style: |
| Round, slotted |
| Shaft Bearing Type: |
| Ball |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 1080.0 |
| Maximum Starting Torque: |
| 0.60 inch-ounces |
| Maximum Running Torque: |

0.40 inch-ounces

NSN 5905-00-498-5873

Precision Wire Wound Variable Resistor - Page 2 of 3



| Maximum Stop Torque: |
|--------------------------------------------------------------------------------|
| 100.00 inch-ounces |
| Shaft Runout: |
| 0.001 inches |
| Lateral Runout: |
| 0.001 inches |
| Shaft Radial Play: |
| 0.001 inches |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Clamp ring |
| Electrical Resistance Per Section: |
| 100.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 1265.0 |
| Function Conformity Tolerance Per Section: |
| -0.25/+0.25 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Function Conformity Per Section: |
| Single section terminal base linearity |
| Fixed Tap Quantity Per Section: |
| 1 single section |
| Tap Location Tolerance Per Section: |
| -5.0/+5.0 ohms single section |
| Resistance Tolerance Per Section In Percent: |
| -1.0/+1.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Tap Location From Ccw Terminal Per Section In Ohms: |
| 5000.0 single section |
| Function Characteristic Per Section: |
| Single section linear |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |

Shelf Life: N/a

4 tab, solder lug

Terminal Type And Quantity:

NSN 5905-00-498-5873

Precision Wire Wound Variable Resistor - Page 3 of 3



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A002a0