

View Online at <https://aerobasegroup.com/nsn/5905-00-499-2134>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.5620 inches

Pilot Length:

0.0600 inches

Overall Length:

3.719 inches

Undercut Diameter:

1.562 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.766 inches

Shaft Diameter:

0.2497 inches

Shaft Length:

0.688 inches

Body Length:

3.000 inches

Overall Diameter:

2.149 inches

Mounting Lip Diameter:

1.7500 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

349.0

Maximum Starting Torque:

0.85 inch-ounces

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

100.000 kilohms 1st section

Rotary Actuator Travel In Angular Deg:

345.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Fixed Tap Quantity Per Section:

1 all sections

Tap Location Tolerance Per Section:

-10.0 to 10.0 ohms all sections

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

500000.0 2nd section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0