NSN 5905-00-500-5517

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-500-5517 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.321 inches **Body Diameter:** 1.000 inches **Shaft Diameter:** Between 0.240 inches and 0.260 inches **Shaft Length:** 0.940 inches **Mounting Bushing Length:** 0.438 inches **Body Length:** 2.321 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Shaft End Play:** 0.00900 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.004 inches **Pilot Diameter Runout:**

0.00200 inches **Shaft Radial Play:**

0.002 inches

NSN 5905-00-500-5517

Precision Wire Wound Variable Resistor - Page 2 of 3



Mechanical Backlash In Deg Angular Rotation:
1.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
110.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-40.0/+40.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-500-5517

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0