NSN 5905-00-500-7152

Precision Wire Wound Variable Resistor - Page 1 of 2



Tresision time treams ramasie resister i age r
View Online at https://aerobasegroup.com/nsn/5905-00-500-7152
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.812 inches
Body Diameter:
0.875 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.270 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.812 inches
Overall Diameter:
0.875 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
0.75 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing

Electrical Resistance Per Section: 2.700 kilohms single section

NSN 5905-00-500-7152 Precision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
1.00/+1.00 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
30.0 single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
4002a0