Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-500-7580

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

2.938 inches

#### **Body Diameter:**

1.266 inches

#### Shaft Diameter:

0.250 inches

### Shaft Length:

2.188 inches

### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.750 inches

### Overall Diameter:

1.633 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

300.0

# Nonturn Device Location:

At 3 oclock

# Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing w/shaft seal

### **Electrical Resistance Per Section:**

50.000 ohms single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Rotary Actuator Travel In Angular Deg:** 

300.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

#### **Special Features:**

0.375 in. Long bushing

#### **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

\_ ... . .

Demilitarization:

No

---

Fiig:

A002a0