NSN 5905-00-500-7731

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-500-7731 **Section Quantity: Shaft Diameter:** 0.219 inches **Shaft Length:** 0.250 inches **Overall Diameter:** 2.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 20.000 kilohms single section **Function Conformity Tolerance Per Section:** -0.50/+0.50 single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 2 single section **Tap Location Tolerance Per Section:** -0.6/+0.6 degrees angular rotation single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Terminal Type And Quantity:** 6 tab, solder lug **Reference Number Differentiating Characteristics:**

Shelf Life:

N/a

As differentiated by ohm resistance

NSN 5905-00-500-7731

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



		• -						
ш	ın	ıt (r 1t	ΝЛ	മാ	CI.	ire:	•

--

Demilitarization:

No

Fiig:

A002a0