NSN 5905-00-500-8700

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-500-8700

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.438 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.188 inches
Mounting Bushing Length:
0.312 inches
Body Length:
0.375 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Screw Thread Diameter:
Screw Thread Diameter.
0.375 inches
0.375 inches
0.375 inches Screw Thread Series Designator:
0.375 inches Screw Thread Series Designator: Unef
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Features Provided:
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Features Provided: Grounded contact arm
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Features Provided: Grounded contact arm Electrical Resistance Per Section:
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Features Provided: Grounded contact arm Electrical Resistance Per Section: 6.000 ohms single section
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Features Provided: Grounded contact arm Electrical Resistance Per Section: 6.000 ohms single section Power Dissipation Rating Per Section In Watts:
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Features Provided: Grounded contact arm Electrical Resistance Per Section: 6.000 ohms single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Features Provided: Grounded contact arm Electrical Resistance Per Section: 6.000 ohms single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section Resistance Tolerance Per Section In Percent:

3 tab, solder lug

Terminal Type And Quantity:

NSN 5905-00-500-8700

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0