

View Online at <https://aerobasegroup.com/nsn/5905-00-501-5176>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

3.625 inches

**Body Diameter:**

1.531 inches

**Shaft Diameter:**

Between 0.249 inches and 0.251 inches

**Shaft Length:**

2.250 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

1.375 inches

**Overall Diameter:**

1.8905 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

20.000 kilohms all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 all sections

**Power Dissipation Rating Per Section In Watts:**

4.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0