Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-501-7288

# Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

### Terminal Length:

0.315 inches

#### Shaft Diameter:

0.130 inches

- Shaft Length:
- 0.030 inches

Body Length:

#### 0.400 inches

Body Width:

### 0.218 inches

**Body Height:** 

0.400 inches

Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

360.0

### **Center To Center Distance Between Terminals:**

0.210 inches

### **Terminal Location:**

Longitudinally positioned on the circumference

### **Mounting Method:**

Terminal

### **Electrical Resistance Per Section:**

5.000 kilohms single section

### **Rotary Actuator Travel In Angular Deg:**

360.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.105 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section



**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

### Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0