NSN 5905-00-501-7545

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



Vie	w Online at https://aerobasegroup.com/nsn/5905-00-501-7545
Se	ction Quantity:
1	
Во	dy Style:
Cyl	indrical bushing mounted
Re	liability Indicator:
No	t established
Ov	erall Length:
1.1	87 inches
Во	dy Diameter:
1.0	94 inches
Sh	aft Diameter:
0.0	63 inches
Sh	aft Length:
0.6	25 inches
Мо	unting Bushing Length:
0.5	00 inches
Во	dy Length:
0.5	62 inches
Sh	aft Style:
Ro	und, slotted
Sh	aft Bearing Type:
Bea	aring
Ac	tuator Type:
Sin	gle shaft
No	nturn Device Location:
At 9	9 oclock
No	nturn Device Radius:
0.5	31 inches
Sc	rew Thread Diameter:
0.3	75 inches
Sc	rew Thread Series Designator:
Un	ef
Sc	rew Thready Qty Per Inch (tpi):
32.	0
Мо	unting Method:
Loc	sking bushing
Ele	ctrical Resistance Per Section:
50.	000 kilohms single section
Po	wer Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

NSN 5905-00-501-7545

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section in Percent	
-10.0 to 10.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0