NSN 5905-00-501-7995

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-501-7995

| 1 |
|---|
| Body Style: |
| Cylindrical hole/slot mounted |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 1.786 inches |
| Body Diameter: |
| 1.750 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.750 inches |
| Body Length: |
| 0.800 inches |
| Overall Diameter: |
| 2.280 inches |
| Mounting Hole/stud Circle Diameter: |
| 0.874 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Double ended shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 320.0 |
| Screw Thread Diameter: |
| 0.138 inches |
| Screw Thread Series Designator: |
| Unc |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Clamp ring and threaded hole |
| Electrical Resistance Per Section: |
| 60.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |

NSN 5905-00-501-7995

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 71.0 single section Power Dissipation Rating Per Section In Watts:

2.5 free air single section

Resistance Tolerance Per Section In Percent:

-3.0 to 3.0 single section

Actuator Travel Control Feature:

Continuous motion

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Terminal @4 not used

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0