## NSN 5905-00-501-8043

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-501-8043

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.750 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.438 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.469 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
Nonturn Device Location: At 9 oclock
At 9 oclock
At 9 oclock  Nonturn Device Radius:
At 9 oclock  Nonturn Device Radius:  0.234 inches
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef
At 9 oclock  Nonturn Device Radius: 0.234 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):  32.0
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:  Locking bushing
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method: Locking bushing  Electrical Resistance Per Section:
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location: Radially positioned over less than half the circumference  Mounting Method: Locking bushing  Electrical Resistance Per Section:  20.000 kilohms single section
At 9 oclock  Nonturn Device Radius:  0.234 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location: Radially positioned over less than half the circumference  Mounting Method: Locking bushing  Electrical Resistance Per Section:  20.000 kilohms single section  Power Dissipation Rating Per Section In Watts:

A single section

**Standard Taper Curve Per Section:** 

## NSN 5905-00-501-8043

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0