

View Online at <https://aerobasegroup.com/nsn/5905-00-501-8554>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.5620 inches

Pilot Length:

0.0620 inches

Overall Length:

2.213 inches

Undercut Diameter:

1.625 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.781 centimeters

Shaft Diameter:

0.250 inches

Shaft Length:

0.563 inches

Body Length:

1.650 inches

Overall Diameter:

2.500 inches

Mounting Lip Diameter:

1.7500 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Ball

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

357.0

Maximum Starting Torque:

1.10 inch-ounces

Maximum Running Torque:

0.70 inch-ounces

Shaft End Play:

0.00250 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.000 percent, rated amperes c and better

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 all sections

Power Dissipation Rating Per Section In Watts:

1.0 7th secondary at 10'30 oclock

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

6 oclock 12th primary

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Special Features:

Rear shaft is 0.125 inches long by 0.250 inches in diameter

Test Data Document:

10001-2552951 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0