Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-501-9680

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Overall Length:**

1.063 inches

### **Body Diameter:**

0.875 inches

Shaft Diameter:

Between 0.123 inches and 0.125 inches

Shaft Length:

0.688 inches

### Mounting Bushing Length:

## 0.250 inches

**Body Length:** 

0.375 inches

### Overall Diameter:

1.094 inches

### Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

320.0

### Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

15.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

360.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0