NSN 5905-00-501-9810

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-501-9810

Section Quantity:
2 Posts State
Body Style:
Cylindrical hole/slot mounted
Reliability Indicator:
Not established
First Flat Length:
1.562 inches
Flat Height:
0.344 inches
Body Diameter:
6.000 inches
Shaft Diameter:
0.375 inches
Shaft Length:
2.000 inches
Mounting Hole/stud Circle Diameter:
2.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
2.375 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
1.3 ohms 1st section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 all sections
Power Dissipation Rating Per Section In Watts:
50.0 free air 2nd section

NSN 5905-00-501-9810

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

Special Features:

Mounted in bracket

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0