Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-501-9810

Section Quantity:

2

Body Style:

Cylindrical hole/slot mounted

Reliability Indicator:

Not established

First Flat Length:

1.562 inches

Flat Height:

0.344 inches

Body Diameter:

6.000 inches

Shaft Diameter:

0.375 inches

Shaft Length:

2.000 inches

Mounting Hole/stud Circle Diameter:

2.375 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Lateral Distance Between Mounting Hole Centers:

2.375 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

20.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

1.3 ohms 1st section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 all sections

Power Dissipation Rating Per Section In Watts:

50.0 free air 2nd section

AeroBase Group

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

Special Features:

Mounted in bracket

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0