NSN 5905-00-502-0285

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-502-0285

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 2.031 inches |
| Terminal Length: |
| 0.344 inches |
| Body Diameter: |
| 1.062 inches |
| Shaft Diameter: |
| Between 0.248 inches and 0.250 inches |
| Shaft Length: |
| 1.469 inches |
| Body Length: |
| 0.562 inches |
| Overall Diameter: |
| 1.404 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 3 oclock |
| Nonturn Device Radius: |
| 0.531 inches |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 1.000 kilohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |

NSN 5905-00-502-0285

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Resistance Tolerance Per Section In Percent: |
|--|
| -10.0 to 10.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Special Features: |
| 0.375 inch long bushing |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A002a0