NSN 5905-00-502-3377

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-502-3377 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.750 inches **Body Diameter:** 1.109 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.969 inches and 1.031 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.719 inches **Overall Diameter:** 1.305 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 0.75 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Shaft Runout:** 0.008 inches **Shaft Radial Play:** 0.008 inches

Fragility Factor:

Moderately delicate

NSN 5905-00-502-3377

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
400.0 ohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
180.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0 to 2.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-502-3377

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



			ati	

No

Fiig:

A002a0