## NSN 5905-00-502-4372

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-502-4372 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.535 inches **Overall Height:** 0.500 inches **Overall Width:** 0.187 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.078 inches **Shaft Length:** 0.035 inches **Body Length:** 0.500 inches **Body Width:** 0.187 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 7200.0 and 16200.0 **Maximum Starting Torque:** 10.00 inch-ounces **Maximum Running Torque:** 0.10 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity:** 2

Terminal Location:
Rear end
Mounting Method:

Unthreaded hole

## NSN 5905-00-502-4372

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 16200.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.7 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0