NSN 5905-00-502-4698

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-502-4698

| Section Quantity: | | | | |
|---|--|--|--|--|
| 1 | | | | |
| | | | | |
| Body Style: | | | | |
| Cylindrical bushing mounted | | | | |
| Reliability Indicator: | | | | |
| Not established | | | | |
| Body Diameter: | | | | |
| 1.375 inches | | | | |
| Shaft Diameter: | | | | |
| 0.250 inches | | | | |
| Shaft Length: | | | | |
| 2.500 inches | | | | |
| Mounting Bushing Length: | | | | |
| 0.500 inches | | | | |
| Body Length: | | | | |
| 1.000 inches | | | | |
| Shaft Style: | | | | |
| Round | | | | |
| Actuator Type: | | | | |
| Single shaft | | | | |
| Nonturn Device Location: | | | | |
| At 9 oclock | | | | |
| Nonturn Device Radius: | | | | |
| 0.531 inches | | | | |
| Screw Thread Diameter: | | | | |
| 0.375 inches | | | | |
| Screw Thread Series Designator: | | | | |
| Unef | | | | |
| Screw Thready Qty Per Inch (tpi): | | | | |
| 32.0 | | | | |
| Terminal Location: | | | | |
| Radially positioned over less than half the circumference | | | | |
| Mounting Method: | | | | |
| Standard bushing | | | | |
| Electrical Resistance Per Section: | | | | |
| 40.000 ohms single section | | | | |
| Power Dissipation Rating Per Section In Watts: | | | | |
| 2.0 free air single section | | | | |
| Resistance Tolerance Per Section In Percent: | | | | |
| -5.0 to 5.0 single section | | | | |

W single section

Standard Taper Curve Per Section:

NSN 5905-00-502-4698

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Terminal | Type | And | Quantity: |
|----------|------|-----|-----------|
|----------|------|-----|-----------|

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0