

View Online at <https://aerobasegroup.com/nsn/5905-00-502-6567>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.6200 inches

Pilot Length:

0.0620 inches

Overall Length:

2.327 inches

Undercut Diameter:

1.820 inches

Undercut Width:

0.0620 inches

Body Diameter:

1.945 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.562 inches

Body Length:

2.062 inches

Overall Diameter:

1.625 inches

Mounting Lip Diameter:

1.8200 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Contact Arm Electrical Off Position:

Fully ccw-cw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

1.30 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Upper adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

1.82000 inches

Electrical Resistance Per Section:

2.200 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0