NSN 5905-00-502-7328

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-502-7328

view Chiline at https://aerobasegroup.com/hsh/5505-55
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Overall Length:
1.187 inches
Body Diameter:
1.250 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.562 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
F 000 bilebook single seeding
5.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
-
Power Dissipation Rating Per Section In Watts:
Power Dissipation Rating Per Section In Watts: 2.0 free air single section

-10.0 to 10.0 single section

NSN 5905-00-502-7328

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0