Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-502-8460

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## Reliability Indicator:

Not established

### **Overall Length:**

1.437 inches

#### Body Diameter:

1.062 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

### Mounting Bushing Length:

## 0.375 inches

**Body Length:** 

0.562 inches

Shaft Style:

Round, slotted

## Shaft Bearing Type:

Bearing

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 3 oclock

#### **Nonturn Device Radius:**

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

100.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0