NSN 5905-00-502-9307

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-502-9307 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.188 inches **Shaft Style:** Round, slotted Switch Type: Rotary **Switch Voltage Rating In Volts:** 10.0 **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 500.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section

500.000 kilohms single section

Power Dissipation Rating Per Section In Watts
0.5 free air single section

Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

Switch Current Type And Rating In Amps:
15.000 ac/dc

NSN 5905-00-502-9307

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
C single section
Terminal Type And Quantity:
3 tab, solder lug and 2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0